

Specifications

SMART kapp 1

SMART kapp™ 42" capture board (kapp42)

Overview


The SMART kapp™ 42" capture board enables you to collaborate with others in a simple but powerful way. Write and draw on the capture board like you would a regular dry erase board. You can then connect a Bluetooth®-enabled mobile device to the capture board by scanning a Quick Response (QR) code or by tapping the Near Field Communication (NFC) tag. When you first connect your mobile device, you're directed to the Apple App Store or Google Play™ to download the SMART kapp app. After you download and install the app, you can use it to connect to your capture board and share content with others.





Dimensions and weights¹

Dimensions



Weight

35 lb. (16 kg)

Shipping dimensions

47 1/4" × 25" × 5 3/8" (119.9 cm × 63.5 cm × 13.6 cm)

Shipping weight

47 lb. (21.3 kg)

 $^{^{1}}$ All dimensions \pm 1/8" (0.3 cm). All weights \pm 2 lb. (0.9 kg).

SMART KAPP 42" CAPTURE BOARD (KAPP42)

Parts and features

Included parts SMART kapp 42" capture board

Dry-erase marker (×3)

Eraser

Bracket and hardware for mounting the capture board to a wall

Digital capture technology

DViT® (Digital Vision Touch) technology

Wireless technology

Bluetooth 2.1 + EDR²

Capture options

Establish a Bluetooth wireless connection with a supported mobile device (see below) by doing one of the following:

• Scan the capture board's unique QR code

• Tap the capture board's NFC tag (Android™ devices only)

Connect a USB drive

USB drive support

USB 2.0 Type-A receptacle

Support for FAT-formatted USB drives only

Mobile device support

Apple devices iOS 7.1 or later operating system software

50 MB storage iPhone 4S or later

Third generation iPad or later First generation iPad mini or later Fifth generation iPod touch or later

Android devices

Android 4.1 (Jelly Bean) or later operating system

50 MB of storage (internal or SD card)

Devices meeting the following specifications:

- 1024 MB of RAM
- 720p or better screen resolution
- Bluetooth 2.1 + EDR
- NFC (recommended)
- 3 megapixel or better rear-facing camera (recommended)

 $^{^{2}}$ Compatible with Bluetooth 3.0 and dual-mode Bluetooth 4.0

Mounting

Options Included mounting bracket

Standard VESA® 400 mm × 400 mm mounting bracket


Recommended height 69" (175.3 cm) from the floor to the middle of the included mounting bracket

Bolt requirements for VESA mounting bracket

Size M6

Maximum length To avoid damage to the capture board, ensure the bolt is no longer than

1/2" (1.2 cm) plus the width of the washer (a) and the width of the bracket (b)



Power

Power specifications 5V, 3A

Power cable 9' 10" (3 m) power cable

Storage and operating requirements

Storage

Temperature -40-140°F (-40-60°C)

Humidity 5–95% relative humidity, non-condensing

Operating

Temperature 41–95°F (5–35°C)

Humidity 10–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification CE, ETL, C-Tick, FCC

Environmental compliance

European Union REACH, RoHS, WEEE and Packaging

U.S. Packaging and Conflict Minerals

SMART KAPP 42" CAPTURE BOARD (KAPP42)

Purchasing information

Order numbers

1024494 SMART kapp 42" capture board (kapp42)

Warranty 90-day limited equipment warranty

Extended warranties

EWY1-KAPP42 One-year extended warranty

EWY2-KAPP42 Two-year extended warranty

Replacement parts Replacement erasers can be purchased from the Store for SMART Parts

(see smarttech.com/Support/PartsStore)

smartkapp.com

© 2014 SMART Technologies ULC. All rights reserved. DViT, kapp, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. Apple, iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android and Google Play are trademarks of Google Inc. The Bluetooth word mark is owned by the Bluetooth SIG, Inc. and any use of such marks by SMART Technologies ULC is under license. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patents. www.smarttech.com/patents. Contents are subject to change without notice. 11/2014.